

POWER LIFT®

POWERFUL IDEAS FOR POWERFUL RESULTS

MULTI-FUNCTIONAL PULLEY UNIT

The Multi-Functional Pulley Unit is a space-saving machine that is available as a free standing, wall mounted, or rack mounted unit. The Multi Functional Pulley Unit features dual handles, a 600 lb. weight stack, 4:1 resistance ratio when 1 handle is used and a 2:1 resistance ratio when both handles are used, 16 adjustment positions, chin and dip handles, and a t-bar ankle attachment. The combination of the chin/dip handles allows users to perform a resisted movement.

KEY FEATURES:

- 600 lb. weight stack features 10 lb. increments with a 5 lb. add on weight. Weight stacks are fully machined steel weight stacks with a powder coat finish.
- 3/16" jacketed to 1/4" Military Grade cables are used on all equipment
- 1" solid chrome guide rods
- 7/16" diameter weight selector pin locks in place and is connected to the weight stack to prevent loss
- Rubber bumpers under each weight stack to reduce vibration
- Top weight plate with free floating bushings for smooth operation
- Steel weight stack guards
- Components are mig .035 welded in jig fixtures ensuring consistent fabrication and tubes have welded end caps
- Standard handles include a 48" Lat pull down, low row handle and nylon strap handle
- Frame: 2" x 2" 11 gauge steel, 1 1/2" 11 gauge steel and various flat steel sizes
- Dip Attachment Dimensions: 36" (L) x 27 1/2" - 20" (W) x 7 1/2" (H) / 24 lbs. (Weight)



Overall Dimensions:

37" (L) x 21" (W) x 94" (H)
1,050 lbs. (Approximate Weight)

Warranty:

Lifetime conditional warranty on frame components. Five years on rotary bearings, guide rods, pulleys and weight plates. One year on belts, cables and grips. Ninety days on upholstery and items not specified.

Part Number:

32603A

powerliftusa.com
800.872.1543

